

**S3 FO SR**  
**EN ISO 20345:2022**  
**36 to 48**



- Full grain leather
- **Softane™ dual-density sole**
- **Steel toe cap / Steel midsole**
- **Antistatic**

- ❖ Brown heavy duty boot.
- ❖ Water-repellent full grain leather, thickness 2.0 / 2.2 mm.
- ❖ Lined padded collar for better ankle and Achilles tendon protection and greater walking comfort.
- ❖ Lace-up, with 5 pairs of stainless triangles. Laces : 90 cm.
- ❖ Bellows tongue provides total waterproofness and protection for the top of the foot.
- ❖ Vamp lining in non-woven fabric, resists scuffing and acid perspiration.
- ❖ Inlay covering the entire surface of the foot, removable, antistatic, treated against bacteria, containing active carbon, anatomical and with heel cushioning. High capacity for absorbing and evaporating perspiration
- ❖ Perforated steel toe-cap (patented) – 200 J.
- ❖ Puncture-resistant stainless steel midsole.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Dual density **Softane™** sole with progressive shock absorber to protect back and joints from vibrations. Self cleaning sole pattern. Multi-directional treads. Rounded heel pressure zone for comfort and stability.

### Slip resistance tests results EN Standard ISO 20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)

A- Heel to the front **0,49** (≥ 0,31)

B- Front to back **0,65** (≥ 0,36)

Additional requirement SR : Ceramic /Glycerin

C - Heel to the front **0,58** (≥ 0,19)

D- Front to back **0,54** (≥ 0,22)

- ✓ Wraps round the foot for increased stability when walking.
- ✓ Outsole density = 1.02 / Comfort layer density = 0.45
- ✓ Highly resistant to oils and hydrocarbons.
- ✓ Abrasion resistance : 80 mm<sup>3</sup>
- ✓ Heel shock absorption 29 Joules.

Weight	Gross Weight (42): 1420 g / Net Weight (42): 1250 g			
Size	36 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	342 x 213 x 114		350 x 245 x 133	
Cartons (mm)	590 x 220 x 348	590 x 437 x 348	685 x 500 x 355	685 x 250 x 358

