

JYJY507 JALELITE SAS

SPECIALS

* Brevet International



EN ISO 20345:2011 S3 CI HI HRO SRC
35 to 48



- Water-repellent full-grain leather upper.
- **SYNERGY Vibram® sole with Infinergy® de BASF**
- Aluminum safety toe cap type B and midsole no metallic
- Antistatic

- ❖ Rangers safety shoe made with anti-fatigue technology.
- ❖ Water-repellent full grain leather upper with pull-up finish, made with a minimum of stitching for longer life. PU defenders for greater toe protection and long life in harsh conditions.
- ❖ Fluorescent markings on sides for increased visibility by night.
- ❖ Two leather tabs, one on the tongue and the other on the back.
- ❖ Upper lined in breathable **3D mesh** with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Ergonomic padded collar with compact flexible foam for extra comfort.
- ❖ **BOA® Fit System** with no lacing. Dial in to fast, effortless, precision fit.
- ❖ Padded and lined leather tongue for instep protection with side bellows to keep out dust and dirt.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable. Anatomical, breathable and fitted with the **Link ESD™** system, innovative multi-contact static electricity dissipater (Patent pending).
- ❖ **PREM-Alu** tip in aluminium type B resisting an impact of an energy of 200 joules. Minimum height after test $\geq 4\text{mm}$ in relation to the Type A toe cap in accordance with Standard 22568-2 : 2021.
- ❖ Stab-resistant structural insole and liner in **FleXtane™ By Jallatte**, in compliance with standard **22568-4 : 2021**, antistatic, 100% composite. Sewn directly onto the upper and covering 100% of the foot for total protection. 100% composite materials: lighter than steel, non-magnetic, non-conductive of heat or cold.
- ❖ **Innovative Synergy** sole in bi-ingredient **CA /PU** and BASF Infinergy® E-TPU (Expanded Thermoplastic PolyUrethane) insert, with a remarkable capacity to reproduce more than 55% of the energy accumulated while (Bounce test **EN ISO 8307**).

Slip resistance tests results EN Standard ISO 20345:2011 Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,73** (>0,32) – On the heel **0,70** (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat **0,30** (>0,18) – On the heel **0,28** (>0,13)

- **Vibram®** rubber outsole with specific studs for outdoor jobs.
- **E-TPU** insert at low density of 0,25.
 - High resistance to abrasion and stretching.
 - Good chemical resistance.
 - Long-term durability in a wide temperature range.
 - **Dynamic performance in 3 phases: Shock Absorption - Accumulation of energy - Dynamic Return.**

Weight	Gross weight (42) : 2146 g / Net weight (42) : 1840 g
Size	35 to 48
Packaging	5 pairs
Box shoes (mm)	337 x 328 x 135
Cartons (mm)	625 x 425 x 343



www.jallatte.com